

Model - EDV-16X



Model EDV-16X is Designed to Remove Condensate from Compressed-Air Systems. Most Suitable for installation. Drip legs, Moisture Separators etc. Valve has facility to drain manually on power failure.

Timer

- Interval Time : 1-128 Min. Adjustable
- Drain Time : 4 Sec. (Other on request)
- Supply Voltage : 230VAC (160-260), 50Hz (Other on request)
- Operating Temp. : 70 C (Maximum)
- Housing Material : High Impact Resistant ABS
- Connection : DIN 43650 A with Power Indication
- Indications : LED (Red)- Power On
LED (Yellow)- 'On' after every 15 sec. Indicate healthiness of timer
LED (Green)- 'On' during drain cycle

Valve


- Type : 2 Way Direct Acting
- In/Out Ports : 1/2" / 3/4" / 1/4" / 1" BSP (F)
- Working Pressure : 16 Kg./cm2
- Valve Body : Bar Stock Aluminium with anodizing (Brass & S.S. On request)
- Orifice : 2.5mm

Features


- Fully Automatic - No Maintenance
- Manual Test Switch
- Indication for valve healthiness
- Easy to replace
- 'O' Ring seal on cycle adjustment pots to ensure weather proof sealing
- Small compact resistant ABS Timer
- 12 Months Warranty
- No tool required to replace timer

Automatic Drain Valve Model : EDV-16X


Model	Orifice	MWP	Connection Size	Features	Application	Remarks
EDV - 161	2.5 mm	16 Kg/cm2	1/2" BSP (F)	Poppet Type, Compact Test Switch, Fault Indication, Inbuilt Strainer	Small Receivers, Moisture Separators, Drip Legs	
EDV - 162	2.5 mm	16 Kg/cm2	1" BSP (F)			
EDV - 163	2.5 mm	16 Kg/cm2	3/4" BSP (F)			
EDV - 164	2.5 mm	16 Kg/cm2	1/4" BSP (F)			



GA / Installation Drawing



Assy. Drawing



Part's Drawing

CONCEPT TECHNOSTRUCTURES
 H - 9 (A), Electronic Complex, I.P.I.A, Road No. 1,
 Kota - 324005 (Rajasthan) India
 Tel. No. : +91-744-2436747 / 9413350063 / 8875009534
 Email : conceptsales1@gmail.com / sales@conceptgroups.com
 Website : www.conceptgroups.com

Available At :

Certificate Number:
 114629/A/0001/UK/En
 ISO 9001:2015

